

Product **FLUXO P578** Reference **TDS224A** Date **01/01/2013** Page **1/1**

## FLUXO P578

Water Washable Fluorescent Penetrant  
Method A/C - Level 2

<b>Standards &amp; Specifications</b>	: <ul style="list-style-type: none"><li>✓ <b>NF EN ISO 3452-2</b> and <b>NF EN 571-1</b></li><li>✓ <b>RCC-M</b></li><li>✓ <b>ASME</b> - Boiler and Pressure Vessel CODE - Section V</li><li>✓ <b>ASTM E 1417</b></li><li>✓ <b>ASTM E 165</b></li><li>✓ <b>Low in Sulphur &amp; Halogens (Nuclear Quality)</b></li></ul>
<b>Product</b>	: Ready-to-use
<b>Composition</b>	: <b>FLUXO P578</b> is a stable solution of petroleum distillates (high flash point), non ionic surfactants and fluorescent dyes.
<b>Health &amp; Safety</b>	: <p><b>FLUXO P578</b> is free from Alkyl Phénol Ethoxylates (APE) - Free from Phtalates, aromatic Phosphate esters and other products suspected carcinogens or neurotoxics.</p> <p><b>FLUXO P578</b> is free from glycol ether (CAS 112-34-5).</p> <p>For more details for Health &amp; Safety information, please refer to the MSDS.</p>
<b>Properties</b>	: <ul style="list-style-type: none"><li>✓ <i>Aspect</i> : Fluorescent mobile liquid</li><li>✓ <i>Density (20°C)</i> : 0,9</li><li>✓ <i>Flash Point</i> : &gt; 100°C</li><li>✓ <i>Viscosity</i> : 8 mm<sup>2</sup>/s (40°C)</li><li>✓ Compatible with any metal &amp; many synthetic materials</li></ul>
<b>Packaging</b>	: Aerosol 500ml NET - 10 and 200 litre drums -
<b>Shelf Life</b>	: 60 months Keep the packaging closed after taking out some of the product.
<b>Use</b>	: <p><i>Companion Materials</i> :</p> <p>developer <b>FLUXO R175</b> remover <b>FLUXO N130</b> solvent <b>FLUXO S190</b></p>
<b>Performance Test</b>	: In order to test the evolution of the performances of detection of the <b>FLUXO P578</b> in time, you can proceed with the reference block type 1 and 2, according to the method described in the standard <b>NF EN ISO 3452-2</b> (standard part reference 1 & 2).

*SREM Technologies can make any modifications*