

Product **FLUXO 4**

Revision 3

Date **20.02.2019**Page **1/5****SECTION 1 - IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY****1.1 Product Identifier**

Name of the product : FLUXO 4

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use : White Contrast Paint for Magnetic Particle Inspection

1.3 Details of the Supplier of the Safety Data Sheet*Manufacturer and Supplier:*

SREM TECHNOLOGIES

14, rue des frères Chappe

Tél : +33 (0)2.43.48.15.10

ZI Ouest

Fax : +33 (0)2.43.45.25.26

72200 La FLECHE - FRANCE

e-mail : info@srem.frwww.srem.fr**1.4 Emergency Telephone Number**

Emergency Telephone Number : INRS +33.(0)1.45.42.59.59

SECTION 2 – HAZARDS IDENTIFICATION**2.1 Classification of the substance or Mixture**

Flammable Liquid, Cat 1


H225: Highly flammable liquid and vapour

Skin Sens, Cat 2

H319 : Causes serious eye irritation

STOT SE, Cat 3

H336 : May cause drowsiness or dizziness

2.2 Labels Elements**Hazards Pictograms****Hazard Statement**

H225: Highly flammable liquid and vapour

H319 : Causes serious eye irritation

H336 : May cause drowsiness or dizziness

EUH066 : Repeated exposure may cause skin dryness or cracking

Precautionary Statement

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P243 Take precautionary measures against static discharge.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

2.3 Other Hazards

Product FLUXO 4 Revision 3 Date 20.02.2019 Page 2/5

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Mixtures

Substance Name	N° CAS N° CE	Classification (1272/2008)	Concentration (%)
Aceton	67-64-1 200-662-2 01-2119471330-49-xxxx	<i>Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336</i>	> 50

Full Test of H phrases: see section 16.

SECTION 4 – FISRT AID MEASURES

4.1 Description of first aid measures

General information	Take off immediately all contaminated clothing and wash it before reuse. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). If unconscious place in recovery position and seek medical advice.
After ingestion	Rinse mouth thoroughly with water. Get medical advice/attention if you feel unwell.
After eye contact	In case of eye irritation consult an ophthalmologist. Rinse immediately carefully and thoroughly with eye-bath or water.
After skin contact	After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation. Consult a physician. Take off immediately all contaminated clothing.
Following inhalation	In case of inhaling spray mist, consult a doctor immediately and show him packing or label. If breathing is irregular or stopped, administer artificial respiration.

4.2 Most important symptoms and effects, both acute and delayed

Respiratory complaints Drowsiness

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5 – FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media: Water spray Water mist Foam Extinguishing powder

Unsuitable extinguishing media: Full Water Jet

5.2 Special Hazards arising from the substance or mixtures

: In case of fire may be liberated: Nitrogen oxides (NOx) Carbon monoxide.

5.3 Advice for Firefighters

: In case of fire: Wear self-contained breathing apparatus.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

: Use personal protection equipment – Provide adequate ventilation

6.2 Environmental Precautions

Product **FLUXO 4** Revision 3 Date **20.02.2019** Page **3/5**

: Do not allow to enter into surface water or drains

6.3 Methods and material for containment and cleaning up

: Absorb with liquid-binding material

6.4 Reference to others sections

: See section 8 & 13

SECTION 7 – HANDLING AND STORAGE

7.1 Precautions for safe handling

All work processes must always be designed so that the following is excluded: Inhalation Skin contact Eye contact
Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

7.2 Conditions for safe storage, including any incompatibilities

Ensure adequate ventilation of the storage area.
Hints on storage assembly: Materials to avoid oxidizing agent
Further information on storage conditions: Keep only in the original container in a cool, well-ventilated place.

7.3 Specific End Uses

: White Contrast Paint for Magnetic Particle Inspection

SECTION 8 – EXPOSURE CONTROLES AND PERSONAL PROTECTION

8.1 Control Parameters

Component	CAS	
Aceton	142-82-5	Long Term Value = 500 ppm Short Term Value = 1000 ppm

8.2 Exposure Controls

Eye/face protection : Suitable eye protection: Eye glasses
Skin protection : Use protective skin cream before handling the product. Hand protection
Suitable gloves type: NBR (Nitrile rubber)
Respiratory protection : Filter type: AX is appropriate (if necessary).
Protective clothing : Body protection: not required.
General health and safety measures: When using do not eat, drink, smoke, sniff.
Wash hands before breaks and after work. After cleaning apply high-fat content skin care cream.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemicals properties:

Aspect : White liquid
Odor : characteristic
Density (active component) : 1000 kg/m³
Flash Point (active component) : < 0°C
Initial boiling Point : 80°C (EN ISO 3405)
Ignition Temperature : > 250°C (ASTM E659)
Explosive Limits : lower : 2.1% upper : 13%
Solubility : not soluble in water

9.2 Others information

Product **FLUXO 4** Revision 3 Date **20.02.2019** Page **4/5**

SECTION 10 – STABILITY AND REACTIVITY

- 10.1 Reactivity** : Reaction with oxidising agent
- 10.2 Chemical Stability** : Stable in normal condition of use
- 10.3 Possibility of Hazardous reactions** : No Data available
- 10.4 Conditions to avoid** : No Data available
- 10.5 Incompatible Materials** : No Data available
- 10.6 Hazardous decomposition products** : No Data available

SECTION 11 – TOXICOLOGICAL INFORMATION

11.1 Information on Toxicological Information

Component	DL50 Oral	DL50 Dermal	CL50 Inhalation
Aceton	> 5000 mg/kg (rat)	> 5000 mg/kg (rabbit)	76 mg/L (rat)

Acute oral toxicity: Data apply to the main component.
Acute dermal toxicity: Data apply to the main component.
Acute inhalation toxicity: Data apply to the main component.

SECTION 12 – ECOLOGICAL INFORMATION

12.1 Toxicity

Component	EL50 (24h) daphnie	LL50 (96h) fish
Aceton	> 1000 mg/L	> 1000 mg/L

- 12.2 Persistence and degradability** : No Data available
- 12.3 Bio accumulative potential** : No Data available
- 12.4 Mobility in soil** : No Data available
- 12.5 Results of PBT and vPvB assessment** : no PBT and vPvB
- 12.6 Other adverse effects**

SECTION 13 – DISPOSAL CONSIDERATIONS

13.1 Waste Treatment methods

Do not reject the product
 Ensure conformity to local disposal regulations.
 Packing is not taken again, they must be eliminated (polyethylene cans)

Product **FLUXO 4**

Revision 3

Date **20.02.2019**Page **5/5****SECTION 14 – TRANSPORT INFORMATION****14.1 UN Number**

1090

14.2 UN proper shipping name

ACETONE

14.3 Transport Hazard Class

ADR / RID : 3

IMDG : 3

IATA : 3

14.4 Packing Group

ADR / RID : II

IMDG : II

IATA : II

14.5 Environmental hazards

No

14.6 Special precautions for users**14.7 Transport in bulk according to Annex II of Marpol 73/78 and the IBC Code****SECTION 15 – REGULATORY INFORMATION****15.1 Safety, health and environmental regulations/legislation specific for the substance/mixture****15.2 Chemical Safety Assessment**

: No data available

SECTION 16 – OTHER INFORMATION

The European regulation imposes that all the H sentences (section 2) appear in this paragraph. According to their concentration in the final product, these sentences do not appear on the label. This is why sentences or initials appearing in this paragraph can not appear on the label.

H sentences (section 2 and 3)

H225 : Highly flammable liquid and vapour

H319 : Causes serious eye irritation

H336 : May cause drowsiness or dizziness

Use : Please refer to Technical Data Sheet