

Product **FLUXO P139 AERO**

Revision

Date **06.03.2019**Page **1/6****SECTION 1 - IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY****1.1 Product Identifier**

Name of the product : FLUXO P139 Aerosol

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use : Red Dye Penetrant for Penetrant Testing

1.3 Details of the Supplier of the Safety Data Sheet*Manufacturer and Supplier:*

SREM TECHNOLOGIES

14, rue des frères Chappe

Tél : +33 (0)2.43.48.15.10

ZI Ouest

Fax : +33 (0)2.43.45.25.26

72200 La FLECHE - FRANCE

e-mail : info@srem.frwww.srem.fr**1.4 Emergency Telephone Number**

Emergency Telephone Number : INRS +33.(0)1.45.42.59.59

SECTION 2 – HAZARDS IDENTIFICATION**2.1 Classification of the substance or Mixture**

Flammable Aerosol, Cat 1

H222: Extremely Flammable Aerosol

H229: Pressurised container: May burst if heated

Skin Dam - Cat 2

H315 - Causes skin irritation

Eye Dam - Cat 2

H319 - Cause serious eye irritation

H412 - Harmful to aquatic life with long lasting effects

2.2 Labels Elements**Hazards Pictograms****Hazard Statement**

DANGER

H222: Extremely Flammable Aerosol

H229: Pressurised container: May burst if heated

H315 - Causes skin irritation

H319 - Cause serious eye irritation

H412 - Harmful to aquatic life with long lasting effects

EUH066 - Repeated exposure may cause skin dryness or cracking.

Precautionary Statement

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P262 Do not get in eyes, on skin, or on clothing.

P273 - Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 IF ON SKIN - Wash with plenty of water

P305 + P351 + P338 IF IN EYES - Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 - IF exposed or concerned: Get medical advice/ attention.

P501 Dispose of contents/container to an approval waste disposal plant.

Product **FLUXO P139 AERO** Revision _____ Date **06.03.2019** Page **2/6**

Special labelling for aerosol cans:

Pressurized container: Do not pierce or burn, even after use - Protect from sunlight - Do not expose to temperatures exceeding 50°C - Do not spray on an open flame or other ignition source - Keep away from heat/sparks/open flames/hot surfaces - No smoking.

2.3 Other Hazards

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Mixtures

Substance Name	N° CAS N° CE	Classification (1272/2008)	Concentration (%)
<i>Propellant :</i> <i>Propane</i> <i>Butane</i>	74-98-6 - 200-827-9 01-2119486944-21 106-97-8 - 203-448-7 01-2119474691-32	<i>Flam. Gas 1 H220</i> <i>Press. Gas</i>	> 30
<i>Hydrocarbures, C11-C14, n-alcanes, isoalcanes, cycliques, <2% aromatiques</i>	64742-47-8 265-149-8 01-2119456620-43	<i>Asp. Tox. 1 (H304)</i> <i>EUH066</i>	> 50
<i>Alcools - C12-15 - éthoxylés, propoxylés</i>	120313-48-6	<i>Skin Corr Cat 2 (H315)</i> <i>Aquatic Acute 1 (H400)</i> <i>H412</i>	2,5 – 10
<i>Alcool éthoxylé C11 C15</i>	68131-40-8	<i>Skin Corr Cat 2 (H315)</i> <i>Eye Dam. Cat 1(H318)</i>	< 2.5

Full Test of H phrases: see section 16.

SECTION 4 – FISRT AID MEASURES

4.1 Description of first aid measures

General information	Take off immediately all contaminated clothing and wash it before reuse. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). If unconscious place in recovery position and seek medical advice.
After ingestion	Rinse mouth thoroughly with water. Get medical advice/attention if you feel unwell.
After eye contact	In case of eye irritation consult an ophthalmologist. Rinse immediately carefully and thoroughly with eye-bath or water.
After skin contact	After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation. Consult a physician. Take off immediately all contaminated clothing.
Following inhalation	In case of inhaling spray mist, consult a doctor immediately and show him packing or label. If breathing is irregular or stopped, administer artificial respiration.

4.2 Most important symptoms and effects, both acute and delayed

Respiratory complaints Drowsiness

4.3 Indication of any immediate medical attention and special treatment needed

Product **FLUXO P139 AERO**

Revision

Date **06.03.2019**

Page **3/6**

No data available

SECTION 5 – FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media: Water spray Water mist Foam Extinguishing powder

Unsuitable extinguishing media: Full Water Jet

5.2 Special Hazards arising from the substance or mixtures

: In case of fire may be liberated: Nitrogen oxides (NOx) Carbon monoxide.

5.3 Advice for Firefighters

: In case of fire: Wear self-contained breathing apparatus.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

: Use personal protection equipment – Provide adequate ventilation

6.2 Environmental Precautions

: Do not allow to enter into surface water or drains

6.3 Methods and material for containment and cleaning up

: Absorb with liquid-binding material

6.4 Reference to others sections

: See section 8 & 13

SECTION 7 – HANDLING AND STORAGE

7.1 Precautions for safe handling

All work processes must always be designed so that the following is excluded: Inhalation Skin contact Eye contact

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

7.2 Conditions for safe storage, including any incompatibilities

Ensure adequate ventilation of the storage area.

Hints on storage assembly: Materials to avoid oxidizing agent

Further information on storage conditions: Keep only in the original container in a cool, well-ventilated place.

7.3 Specific End Uses

: Red Dye Penetrant for Penetrant Testing

SECTION 8 – EXPOSURE CONTROLES AND PERSONAL PROTECTION

8.1 Control Parameters

Component	CAS	
Hydrocarbures, C11-C14, n-alcanes, isoalcanes, cycliques, <2% aromatiques	64742-47-8	Long Term Value = 1000 ppm Short Term Value = 1500 ppm
Butane	106-97-8	Long Term Value = 800 ppm = 1900 mg/m ³

8.2 Exposure Controls

Eye/face protection : Suitable eye protection: Eye glasses

Product **FLUXO P139 AERO** Revision _____ Date **06.03.2019** Page **4/6**

Skin protection : Use protective skin cream before handling the product. Hand protection
Suitable gloves type: NBR (Nitrile rubber)
Respiratory protection : Filter type: AX is appropriate (if necessary).
Protective clothing : Body protection: not required.
General health and safety measures: When using do not eat, drink, smoke, sniff.
Wash hands before breaks and after work. After cleaning apply high-fat content skin care cream.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemicals properties:

Physical State : Aerosol
Aspect : Red
Odor : characteristic
Density (active component) : 855 kg/m³
Flash Point (active component) : > 82°C
Viscosity : 3 mm²/s (40°C)
Initial boiling Point : > 200°C (EN ISO 3405)
Ignition Temperature : > 250°C (ASTM E659)
Explosive Limits : lower : 0.5% upper : 6%
Solubility : partially soluble in water

9.2 Others information

SECTION 10 – STABILITY AND REACTIVITY

10.1 Reactivity

: Reaction with oxidising agent

10.2 Chemical Stability

: Stable in normal condition of use

10.3 Possibility of Hazardous reactions

: No Data available

10.4 Conditions to avoid

: No Data available

10.5 Incompatible Materials

: No Data available

10.6 Hazardous decomposition products

: No Data available

SECTION 11 – TOXICOLOGICAL INFORMATION

11.1 Information on Toxicological Information

Component	DL50 Oral	DL50 Dermal	CL50 Inhalation
Hydrocarbures, C11-C14, n-alcanes, isoalcanes, cycliques, <2% aromatiques	> 2000 mg/kg (rat)	> 5000 mg/kg (lapin)	> 5000 mg/m ³ (rat)

Acute oral toxicity: Data apply to the main component.

Acute dermal toxicity: Data apply to the main component.

Acute inhalation toxicity: Data apply to the main component.

Product **FLUXO P139 AERO**

Revision

Date **06.03.2019**

Page **5/6**

SECTION 12 – ECOLOGICAL INFORMATION

12.1 Toxicity

Component	EL50 (24h) daphnie	LL50 (96h) fish
Hydrocarbures, C11-C14, n-alcane, isoalcane, cycliques, <2% aromatiques	> 1000 mg/L	> 1000 mg/L

12.2 Persistence and degradability

: No Data available

12.3 Bio accumulative potential

: No Data available

12.4 Mobility in soil

: No Data available

12.5 Results of PBT and vPvB assessment

: no PBT and vPvB

12.6 Other adverse effects

SECTION 13 – DISPOSAL CONSIDERATIONS

13.1 Waste Treatment methods

Do not reject the product
Ensure conformity to local disposal regulations.
Packing is not taken again, they must be eliminated (polyethylene cans)

SECTION 14 – TRANSPORT INFORMATION

14.1 UN Number

1950

14.2 UN proper shipping name

AÉROSOLS, FLAMMABLE

14.3 Transport Hazard Class

ADR / RID : 2
IMDG : 2
IATA : 2.1

14.4 Packing Group

ADR / RID : No - Instruction LQ2 (LIMITED QUANTITY)
IMDG : No - Instruction LQ2 (LIMITED QUANTITY)
IATA :

14.5 Environmental hazards

No

14.6 Special precautions for users

14.7 Transport in bulk according to Annex II of Marpol 73/78 and the IBC Code

Product **FLUXO P139 AERO**

Revision

Date **06.03.2019**

Page **6/6**

SECTION 15 – REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance/mixture

15.2 Chemical Safety Assessment

: No data available

SECTION 16 – OTHER INFORMATION

The European regulation imposes that all the H sentences (section 2) appear in this paragraph. According to their concentration in the final product, these sentences do not appear on the label. This is why sentences or initials appearing in this paragraph can not appear on the label.

H sentences (section 2 and 3)

- H220 : Extremely flammable Gas
- H222 : Extremely Flammable Aerosol
- H229 : Pressurised container : May burst if heated
- H304: May be fatal if swallowed and enters airways
- H315: Causes skin irritation
- H318: Causes serious eye damage
- H400: Very toxic to aquatic life
- H412: Harmful to aquatic life with long lasting effects

Use : Please refer to Technical Data Sheet